

# JIT SILICONES +

## 877 Paste

### High Temp & Load Solid Paste Lubricant

877 Paste is a multi-purpose, heavy duty lubricating paste containing a blend of solid lubricants in a silicone oil.

It aids in the prevention of galling during run-in of components, helps extend the service life of moving parts, and helps protect against fretting wear and corrosion of metal components.



#### Standard package size:

ITEM #	SIZE	NOTE
22010	5 gm packet	Box of 1500
22011	5.3oz tube	box of 12
22013	8lb pail (1gal)	Plastic Pail
22014	40lb (5 gal)	Plastic Pail
22015	440lb (55 gal)	Metal Drum

## JIT Silicones +

P.O. Box 24  
Mars, PA 16046  
Phone: (855) JIT-PLUS (855) 548-7587

[www.jitsiliconesplus.com](http://www.jitsiliconesplus.com)

Available from:

**877 Paste**

**FEATURES**

- Excellent water resistance
- High temperature lubrication
- Minimizes corrosion

**COMPOSITION**

- Silicone Oil
- Solid lubricant
- Additives

**APPLICATIONS**

- Press fit of metal to metal components
- brake anchor plates and pistons
- Assembly Lubricant - protects metal to metal components during initial assembly and startup

*877 Paste* is formulated with a Silicone base oil and solid lubricants. This material is designed to protect metal on metal slow speed surfaces. It is an excellent product to lubricate during run-in of metal to metal components and can be used at high temperatures. At high temperatures, the oil will flash off and leave the solid particles behind to reduce friction and wear.

**TYPICAL PROPERTIES**

The values reported on this sheet should not solely be used for preparing specifications on this product. Please contact JIT Silicones Plus for assistance in preparing a specification.

<b>Property</b>	<b>Test Method</b>	<b>Typical Value</b>
Color	Visual	Gray/Black
Base Oil		Silicone
Solid Lubricants containing:		Moly/Graphite
Penetration, worked	ASTM D217	331
Service Temperature Range		-49° to 662°F*

\* Base oil temperature limitation 446°F, solid lubricants capable of 662°F

**PACKAGING**

*877 Paste* is available in 5gram packets, 4.5 kg pails (1 gallon), 40lb pails (5 gallon) and 440lb drums (55 gallon). Special container sizes on request.

**Usable Life & Storage** -- When stored at or below 20°C (68°F), this product has a minimum usable life of 36 months from date of production.

**Handling Precautions** - See SDS Sheet

**Limited Warranty - Please Read Carefully**The information contained herein is offered in good faith and is believed to be accurate. However, Because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that JIT Silicones + (JIT) products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

JIT's sole warranty is that the product will meet the sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. JIT SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. JIT DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.