

JIT SILICONES +

Advanced Polymer

High Strength Paintable Sealant

- Primary Use:
Sealing and Bonding:
 - RV & Truck
 - Construction
 - Metal Roofing & Buildings
 - Industrial Applications
- Permanently Flexible Long Lasting Seal
- Service Temperature -40° F to 200° F
- Non-Yellowing
- Excellent Weatherability
- Superior to Polyurethane Sealants
- Removable Nozzle on Cartridges
- Bonds to most substrates
- No Solvents
- No Isocyanates
- VOC Compliant
- ECO Friendly



Standard package sizes:

ITEM #	SIZE	NOTE
10039 (white)	10.1 oz (300ml) Cartridge	12 Cartridges Per Standard Box
10040 (white)	5 gallon pail	Plastic Pail
10041 (white)	55 gallon drum	Metal Drum

Custom Colors Available!

JIT Silicones +

P.O. Box 24

Mars, PA 16046

Phone: (855) JIT-PLUS (855) 548-7587

www.jitsiliconesplus.com

Available from:



Property	Advanced Polymer	Polyurethane	Silicone
Environmental friendliness	10	5	9
Non-bubbling	10	6	10
Low temperature gunnability	10	8	10
Slump resistance	10	10	10
Quick cure	10	7	10
Storage stability	10	7	9
Body (tooling)	8	10	8
Weather resistance	8	6	10
Adhesion to various substrates	10	5	8
Mechanical properties	10	10	10
Non-dirt pickup	10	10	5
Stain resistance	8	8	5
Paintability with water-based paint	10	10	3

1 = Low Performance; 10 = High Performance

PERFORMANCE SPECIFICATIONS:

Exceeds the requirements of ASTM C 920, Type S, Grade NS, Class 25, Use NT, M, G and A

- Federal Specification TT-S-00230C, Type II, Class A
- CAN/CGSB-19 13-M87
- AAMA 808.3-92 Exterior Perimeter Sealing

Skin Over Time: <20min @77F & 50% Relative Humidity
 Tack Free Time: <60min @77F & 50% Relative Humidity
 Lap Shear: 190PSI
 Tensile: 205PSI
 VOC content: 9g/L
 Elongation at break: 300-400%
 Hardness: 35+/-5 Durometer (shore A)

JIT Silicones +

P.O. Box 24

Mars, PA 16046

Phone: (855) JIT-PLUS (855) 548-7587

www.jitsiliconesplus.com