GENERAL PURPOSE SEALANT - ALUMINUM

Version: Revision	on Date: MS	SDS Number:	Date Completed:
2.0 03/202	20 GHS	IS – 15017 – GP-AL	03/2020

SECTION 1. IDENTIFICATION

Product Name:	General Purpose Sealant - Aluminum	
Manufacturer or supplier's details Company name of supplier:	JIT Silicones Plus	
Address:	5 Industrial Park Drive Oakdale, PA 15071	
Telephone:	855-548-7587	
Emergency Telephone:	24 Hour Emergency Telephone: CHEMTREC: (800) 424-9300	
Recommended use of the chemical and restrictions on use		

Recommended use of the chemical and restrictions on use Recommended use: Adhesive, binding agents

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Not a hazardous substance or mixture.	in accordance with 29CFR 1910.1200
GHS Label Element	
Not a hazardous substance or mixture. Precautionary Statements:	Prevention: Use only outdoors or in a well-ventilated area.
Other hazards:	No data available

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature:	Silicone elastomer
Hazardous Ingredients:	Contains no hazardous ingredients according to GHS

GENERAL PURPOSE SEALANT - ALUMINUM

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	03/2020	GHS – 15017 – GP-AL	03/2020

SECTION 4. FIRST AID MEASURES

Inhalation:	Move person to fresh air and keep comfortable for breathing. Consult a physician.
Skin contact:	Wash off with plenty of water
Eye contact: If swallowed: Most important symptoms and effects, both agute and delayed:	Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several minutes. If effects occur, consult a physician, preferably an ophthalmologist No emergency medical treatment necessary Aside from the information found under Description of first aid measure (above) and indication of immediate medical attention
both acute and delayed:	measure (above) and indication of immediate medical attention And special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology information
Protection of first-aiders:	No special precautions are necessary for first aid responders.
Indication of any immediate medical attention and special treatment needed Notes to Physician:	No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)
Unsuitable extinguishing media:	None known.
Special hazards arising from the substance or mixture: Hazardous combustion products:	Carbon oxides Silicon oxides Formaldehyde
Unusual Fire and Explosion Hazards:	Exposure to combustion products may be a hazard to health.
Advice for firefighters	Fire Fighting Procedures: Use water spray to cool unopened containers. Evacuate area. Fire residues and contaminated extinguishing water must be disposed of in accordance with

GENERAL PURPOSE SEALANT - ALUMINUM

2.0 03/2020 GHS – 15017 – GP-AL 03/2020	Version:	Revision Date:	MSDS Number:	Date Completed:
	2.0	03/2020	GHS – 15017 – GP-AL	03/2020

local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from the fire area if it is safe to do so. Special protective equipment for firefighters: Wear self-

contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions:	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up:	Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Conditions for safe storage:	Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. Keep in properly labelled containers. Store in accordance with the particular national regulations.
Do not store with the following product types:	Strong oxidizing agents.
Unsuitable materials for containers:	None known

GENERAL PURPOSE SEALANT - ALUMINUM

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	03/2020	GHS – 15017 – GP-AL	03/2020

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable

Exposure controls	
Engineering Controls	Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.
Individual protection measures	
Respiratory protection:	General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
Eye/face protection:	Use safety glasses (with side shields)
Skin protection:	Hand protection: Use gloves chemically resistant to the material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl Rubber, Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove

GENERAL PURPOSE SEALANT - ALUMINUM

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	03/2020	GHS – 15017 – GP-AL	03/2020

Other protection: Skin and body protection:	supplier. Wear clean, body-covering clothing. Skin should be washed after contact.
Respiratory protection:	Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements of guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Paste
Color:	In accordance with the product description
Odor:	Acetic acid
Odor Threshold:	No data available
рН:	Not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	Not applicable
Flash point:	>100°C (212°F) Method: closed cup
Evaporation rate:	Not applicable
Flammability (solid, gas):	Not classified as a flammability hazard
Upper explosion limit:	No data available
Lower explosion limit:	No data available
Vapor pressure:	Not applicable

GENERAL PURPOSE SEALANT - ALUMINUM

2.0 03/2020 GHS – 15017 – GP-AL 03/2020	Version:	Revision Date:	MSDS Number:	Date Completed:
	2.0	03/2020	GHS – 15017 – GP-AL	03/2020

Relative vapor density:	No data available
Relative density:	1.007
Solubility./(ies) Water solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Autoignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity Viscosity, dynamic:	Not applicable
Explosive properties:	Not explosive
Oxidizing properties:	The substance or mixture is not classified as oxidizing.
Molecular weight:	No data available
NOTE:	The physical data presented above are typical values and should not be construed as a specification

SECTION 10. STABILITY AND REACTIVITY

Reactivity:	Not classified as a reactivity hazard.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required.
Conditions to avoid:	None known.
Incompatible materials:	Oxidizing agents.
Hazardous decomposition products:	Can include and are not limited to: Formaldehyde

GENERAL PURPOSE SEALANT - ALUMINUM

2.0 03/2020 GHS – 15017 – GP-AL 03/2020	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity:

(represents short term exposures with immediate effects – no chronic/delayed effects known unless otherwise noted)

Product:

Acute oral toxicity:	Very low toxicity if swallowed. Harmful
	effects not anticipated from swallowing small
	amounts.
	As product: Single dose oral LD50 has not
	been determined.
	Based on information for component(s):
	LD50, Rat, > 5,000 mg/kg Estimated.
Acute dermal toxicity:	Prolonged skin contact is unlikely to result in
	absorption of harmful amounts.
	As product: The dermal LD50 has not been
	determined. Based on information for
	component(s):
	LD50, > 2,000 mg/kg Estimated.
Acute inhalation toxicity:	Brief exposure (minutes) is not likely to cause
	adverse effects. Vapor from heated material
	may cause respiratory irritation.
	As product: The LC50 has not been
	determined.
Skin corrosion/irritation	Based on information for component(s):
	Prolonged exposure not likely to cause
	significant skin irritation.
	May cause drying and flaking of the skin.
Serious eye damage/eye irritation	Based on information for component(s):
	May cause slight temporary eye irritation.
	Corneal injury is unlikely.
	May cause mild eye discomfort.

Sensitization

GENERAL PURPOSE SEALANT - ALUMINUM

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	03/2020	GHS – 15017 – GP-AL	03/2020

Acute toxicity:

(represents short term exposures with immediate effects – no chronic/delayed effects known unless otherwise noted)

Product:	
Acute oral toxicity:	Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. As product: Single dose oral LD50 has not been determined.
	Based on information for component(s):
Acute dermal toxicity:	LD50, Rat, > 5,000 mg/kg Estimated. Prolonged skin contact is unlikely to result in absorption of harmful amounts. As product: The dermal LD50 has not been
	determined. Based on information for component(s):
Acute inhalation toxicity:	LD50, > 2,000 mg/kg Estimated. Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.
Chin correction (irritation	As product: The LC50 has not been determined. Based on information for component(c):
Skin corrosion/irritation	Based on information for component(s): Prolonged exposure not likely to cause significant skin irritation. May cause drying and flaking of the skin.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

No data available

Persistence and degradability No data available

Bioaccululative potential No data available

Mobility in soil No data available

GENERAL PURPOSE SEALANT - ALUMINUM

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	03/2020	GHS – 15017 – GP-AL	03/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods Resource Conservation and Recovery Act (RCRA):	DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INTENDED CONDITION AS DESCRIBED IN SDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destructive device. For additional information, refer to Handling & Storage Information, SDS Section 7 - Stability & Reactivity Information, SDS Section 10 Regulatory Information, SDS Section 15.
Treatment and disposal methods of used packaging:	Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

SECTION 14. TRANSPORT CONSIDERATIONS

DOT	Not regulated for
	transport
Classification for SEA transport (KMO-IMDG)	Not regulated for
	transport
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC	Consult IMO
Code	regulations before
	transporting ocean
	bulk
Classification for AIR transport (IATA/ICAO):	Not regulated for
	transport
This information is not intended to convey all specific regulatory or operation	hal

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through and authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the aterial.

GENERAL PURPOSE SEALANT - ALUMINUM

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	03/2020	GHS – 15017 – GP-AL	03/2020

SECTION 15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III
(Emergency Planning and Community Right-to-Know Act of 1986)
Sections 311 and 312

SARA 311/312 Hazards:	No SARA Hazards.	
SARA 313: The following components are subject to reporting levels established by SARA Title III, Section 313:	Components: Alum	inum CASRN 7429-90-5
	The following chemi	cals are listed because of the
US State Regulations	additional requirem	ents of Pennsylvania law:
Pennsylvania Right To Know		
Dimethyl siloxane, hydrox	yl-terminated	70131-67-8
Silicon dioxide		7631-86-9
Siloxanes and silicone, din	nethyl	63148-62-9
Titanium dioxide		13463-67-7
Iron oxide		1332-37-2
Aluminum		7429-90-5
Carbon Black		1333-86-4
California Prop 65	This product contain	s a chemical that is at or below
United States TSCA Inventory (TSCA)	California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label. All components of this product are in compliance with the inventory listing requirements of the U.S> Toxic Substances Control Act (TSCA) Chemical Substance Inventory.	

SECTION 16. OTHER INFORMATION

Hazard Rating System

NFPA:

Health	Flammability	Instability
0	1	0

GENERAL PURPOSE SEALANT - ALUMINUM

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	03/2020	GHS – 15017 – GP-AL	03/2020
	•	•	•

HMIS:

Health	Flammability	Physical Hazard
0/	1	0

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw -Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIOC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN -United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

JIT SILICONES PLUS urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all

GENERAL PURPOSE SEALANT - ALUMINUM

	MSDS Number:	Date Completed:
2.0 03/2020	GHS – 15017 – GP-AL	03/2020

federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.