# **ELECTRICAL COMPOUND**

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

#### **SECTION 1. IDENTIFICATION**

Product Name: Electrical Compound

Manufacturer or supplier's details

Company name of supplier: JIT Silicones Plus

Address: 5 Industrial Park Drive

Oakdale, PA 15071

Telephone: 855-548-7587

Emergency Telephone: 24 Hour Emergency Telephone:

CHEMTREC: (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use: Lubricant (not for medical purposes)

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS Classification: Not hazardous

Labeling:

Symbol: None Signal Word: None

Hazardous Statements: Not hazardous

**Precautionary Statements:** Use personal protective equipment as required.

Wear safety glasses and gloves.

Avoid contact with eyes.

Non flammable or combustible, but may burn if involved in a

fire.

# **ELECTRICAL COMPOUND**

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identify: Dimethyl siloxanes and silicones, >90%

Common Name: Methyl silicone

**CAS Number:** 63148-62-9

Impurities: No information provided by manufacturer

Chemical Identify: Silicon dioxide, amorphous, <10%

Common Name: Amorphous fumed silica

**CAS Number:** 112945-52-5

**Impurities:** Less than 1%, not classifiable

### **SECTION 4. FIRST AID MEASURES**

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms

persist, get medical attention. Obtain medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms

persist, get medical attention. No need for first aid is

anticipated.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If

signs/symptoms persist, get medical attention.

**Ingestion:** If swallowed, do not induce vomiting. If irritation or discomfort

occurs, obtain medical assistance.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Autoignition Temperature: >300°C

Flash Point: >300°C

Flammable Limits (LEL): Not determined

Flammable Limits (UEL) Not determined

## ELECTRICAL COMPOUND

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

**Suitable Extinguishing Media:** On large fires use dry chemical, foam, or water spray.

On small fires use carbon dioxide, dry chemical, or water spray.

Water can be used to cool fire exposed containers.

Unsuitable Extinguishing Media: None

Specific hazards in case of fire: Decomposes on heating and can release formaldehyde. Avoid

reaction with oxidizers.

Special protective equipment and precautions for firefighters:

No acute hazard. Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self-contained breathing apparatus with a full face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed

containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so,

remove containers from path of fire.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Use appropriate personal protection. (See section 8.)

**Environmental precautions:** For larger spills, cover drains and build dikes to prevent entry

into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities.

Dispose of collected material as soon as possible.

Methods for material

containment and cleaning up:

Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

### **SECTION 7. HANDLING AND STORAGE**

**Precautions for safe handling:** Avoid contact with skin, inhalation of mist, or ingestion. See

section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated.

# ELECTRICAL COMPOUND

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

Conditions for safe handling, including any incompatibilities:

Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open,

inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined

fiber containers. Keep away from heat and flame.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control Parameters:** Under most handling conditions, this product will not generate

mist or dust.

**Engineering Controls:** In most conditions, no special local ventilation is needed.

General ventilation recommended. If the product is heated

above 150°C or atomized ventilation should be used.

**Personal Protective Equipment** 

(PPE):

**Eyes:** Safety glasses recommended.

**Skin:** Impermeable gloves should be worn. Product is compatible

with most elastomers.

**Inhalation:** No respiratory protection required under most conditions. If

concentrations exceed exposure limits, approved respiratory

equipment must be used.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical state:** Solid. Liquid may separate from product.

**Color:** Off white, translucent

Odor: Mild

Odor Threshold: Not available

pH Value: Not applicable

Melting Point: Decomposes

Freezing Point: Becomes very stiff with decreasing temperature around -60°C

Initial Boiling Point: >200° C

# **ELECTRICAL COMPOUND**

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

Flash Point: >300°C COC (Base oil)

**Evaporation rate:** Not available

Flammability (solid, gas): Not applicable

**Explosion limits:** Not available

Vapor pressure: Negligible at 20°C

Vapor density: Not available

**Solubility:** Insoluble in water at 20°C

Partition coefficient: Not available

Auto-Ignition temperature: Not available

**Decomposition temperature:** Not available

### **SECTION 10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable under ambient temperatures and pressures.

**Possibility of hazardous reactions:** May react with air under high pressure. Otherwise will not

react or polymerize.

Conditions to avoid: No specific conditions to avoid have been identified.

Materials to avoid: Oxidizers

Hazardous decomposition products: Decomposes on heating and produces formaldehyde, silicone

dioxide, and incompletely burned carbon compounds.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

(a) eAcute toxicity: Not toxic. LD50 (rat) > 10,000 mg/kg

(dimethyl silicone)

**(b) Skin corrosion/irritation:** Not irritating / not corrosive to the skin.

LD50 (rabbit) > 2,000 mg/kg

(c) Serious eye damage/irritation: Possible irritant / not corrosive to the eyes.

# **ELECTRICAL COMPOUND**

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

(d) Respiratory or skin sensitization: Not sensitizing to the skin.

(e) Germ-cell mutagenicity: Not a germ cell mutagen.

(f) Carcinogenicity: Not a carcinogen.

(g) Reproductive toxicity: There are currently no reliable scientific data

available indicating adverse effects on

reproduction or fertility.

(h) Aspiration hazard: Not applicable (not an aerosol/mist).

### **SECTION 12. ECOLOGICAL INFORMATION**

#### Toxicity:

Invertebrates: Daphnia magna 48h-LC50>10,000 mg/L (dimethyl silicone) Invertebrates: Daphnia magna 24h-LC50>10,000 mg/L (amorphous silica) Fish: Brachydanio rerio 96h-LC50>10,000 mg/L (amorphous silica)

#### Persistence and degradability

In soil, siloxanes are degraded.

#### **Bioaccumulative potential**

Not expected to bioaccumulate.

#### Mobility in soil

Siloxanes are removed from water by sedimentation or binding to sewage sludge. Silica is not mobile.

#### SECTION 13. DISPOSAL PROCEDURES

Waste treatment methods: Waste (substance and container material) shall be

recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or

dispose of in an authorized landfill.

**According to the European Waste** 

Catalogue:

Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.

For USA Disposal: Waste must be disposed of in accordance with federal,

state, and local environmental control regulations.

# **ELECTRICAL COMPOUND**

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

### **SECTION 14. TRANSPORT INFORMATION**

Class or Type:

US DOT, IMO, ADR, RID, AND, IMDG, and IATA: Non-hazardous.

# **ELECTRICAL COMPOUND**

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

#### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the mixture:

Other Information:

**U.S. Regulatory Information** 

TSCA Inventory Status: All ingredients listed or exempt

TSCA 12 (b) Export Notification: Not listed

CERCLA Section 103 (40 CFR 302.4): N
SARA Section 302 (40 CFR 355.30): N
SARA Section 304 (40 CFR 355.40): N
SARA Section 313 (40 CFR 372.65): N
OSHA Process Safety (29 CFR 1910.119): N

SARA Hazard Categories, SARA Sections

311/312 (40 CFR 370.21) -

Acute Hazard: N
Chronic Hazard: N
Fire Hazard: N
Reactivity Hazard: N
Sudden Release Hazard: N

State Regulations: Not on California Proposition 65 list.

Does not contain any contaminants or by-products known to the State of California to cause cancer or

reproductive toxicity.

**Note:** There are no known safety, health or

environmental restrictions or prohibitions in any country where this product is produced, imported

or marketed.

### **Chemical Inventories:**

DSL (Canada)	All ingredients listed or exempt
IECSC (Peoples Republic of China)	All ingredients listed or exempt
TSCA (United States of America)	All ingredients listed or exempt

# **ELECTRICAL COMPOUND**

Version:	Revision Date:	MSDS Number:	Date Completed:
4.0	01/2015	GHS – 20011-15-ELCMPD	10/2015

#### **SECTION 16. OTHER INFORMATION**

#### NFPA Hazard Classification:

Health: 1
Flammability 1
Reactivity: 0
Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **HMIS Hazard Classification:**

Health 1
Flammability 1
Reactivity: 0

Protection: B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.