DIMETHYL SILICONE FLUID 350CS

 Version:
 Revision Date:
 MSDS Number:
 Date Completed:

 2.0
 10/2020
 GHS-30032-33-DSF-350CS
 10/2020

SECTION 1. IDENTIFICATION

Product Name: Dimethyl Silicone Fluid 350cSt (centistokes)

Manufacturer or supplier's details

Company name of supplier: JIT Silicones Plus

Address: 5 Industrial Park Drive

Oakdale, PA 15071

Telephone: 855-548-7587

Emergency Telephone: 24 Hour Emergency Telephone:

CHEMTREC: (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use: Process regulators,

other than polymerization or vulcanization processes

Lubricants and Lubricant additives

Intermediate Cosmetics

Anti set off and adhesive agents

Additives

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification:

Not a hazardous substance or mixture.

GHS Label element:

Not a hazardous substance or mixture.

Other hazards:

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture: Substance

Substance name: Dimethyl siloxane

CASRN.: 63148-62-9

Synonyms: Siloxane, dimethyl

Hazardous Ingredients: No hazardous ingredients according to GHS

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

SECTION 4. FIRST AID MEASURES

Inhalation: If inhaled, remove to fresh air.

If effects occur, consult a physician.

Skin

contact: Wash off with plenty of water.

Eye Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2

contact: minutes and continue flushing for several additional minutes. If effects occur, consult a physician,

preferably an ophthalmologist.

Ingestion: Rinse Mouth with water. No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control

of symptoms and the clinical condition of the patient.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO2).

Dry chemical.

Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to

health.

Advice for firefighters

Fire Fighting Procedures: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Soak up with inert absorbent material. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

See sections: 7, 8, 11, 12 and 13.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Appearance:

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate prefilter.

Liquid

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Colorless
Odor:	None
Odor Threshold:	No data available
рН:	No data available
Melting Point/freezing Point::	No data available
Initial boiling point and boiling range:	> 35° C (>95° F)
Flash point:	>120° C (248° F) Method: closed cup
Evaporation rate:	No data available
Flammability (solid, gas):	Not applicable
Upper Explosion limit:	No data available

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

Lower Explosion limit: No data available

Vapor pressure: No data available

Relative vapor density: No data available

Relative density: 0.97

Solubility(ies):

Water solubility: No data available

Partition coefficient: No data available

n-octanol/water:

Autoignition Temperature: No data available

Decomposition temperature: No data available

Viscosity

Viscosity, kinematic 350 cSt at 25° C (77° F)

Explosive properties: Not explosive

Oxidizing properties: The substance or mixture is not classified as oxidizing.

Molecular weight: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical Stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

When heated to temperatures above 150° C (300° F) in the presence of air, trace quantities of formaldehyde may be

released.

Adequate ventilation is required.

See OSHA formaldehyde standard, 29CFR 1910.1048. Hazardous decomposition products will be formed at

elevated temperatures.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents.

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

Hazardous decomposition products:

Thermal decomposition include, but are not limited to

Thermal decomposition: Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

Based on product testing:

LD50, Rat, > 48,500 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Based on product testing:

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor form heated material or mist may cause respiratory irritation.

The LC50 has not been determined.

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

Based on product testing: Essentially non-irritating to eyes

Sensitization

For skin sensitization:

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization: No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For this family of materials:

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

For this family of materials: Did not cause cancer in long-term animal studies which used routes of exposure considered relevant to industrial handling. Positive results have been reported in other studies using routes of exposure not relevant to industrial handling.

Teratogenicity

For this family of materials: Did not cause birth defects or any other fetal effects in laboratory animals.

Reproductive toxicity

For this family of materials: In animal studies, did not interfere with reproduction.

Mutagenicity

For this family of materials: In vitro genetic toxicity studies were negative.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50>100mg/L in the most sensitive species tested)

LC50, Fish, 96 Hour, >100mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 hour, >100mg/L

Acute toxicity to algae/aquatic plants

EC50, algae, 14d, >2000mg/l

Long-term (chronic) aquatic hazard

Chronic toxicity to fish

NOEC, Cyprinodon variegatus (sheepshead minnow), 33d, 91mg/l

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

Toxicity to Above Ground Organisms

Material is practically non-toxic to birds on an acute basis (LD50>2000mg/kg).

Oral LD50, Colinus virginianus (Bobwhite quail), >5000mg/kg

Persistence and degradability

The product is not biodegradable

Bioaccumulative potential

No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000)

Mobility in soil

Expected to be relatively immobile in soil (Koc>5000)

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

SECTION 14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk Consult IMO regulations before transporting ocean bulk

according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

No SARA Hazards

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103 This material does not contain any components with a CERCLA RQ.

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components

Siloxanes and silicones, dimethyl 63148-62-9

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

CASRN

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SECTION 16. OTHER INFORMATION

Hazard Rating System NFPA

Health	Flammability	Instability
0	1	0

HMIS

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

Health	Flammability	Physical Hazard
0/	1	0

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw -Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx -Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

JIT Silicones Plus urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the

DIMETHYL SILICONE FLUID 350CS

Version:	Revision Date:	MSDS Number:	Date Completed:
2.0	10/2020	GHS-30032-33-DSF-350CS	10/2020

manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer- specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.