Dielectric Compound

Version:	Revision Date:	MSDS Number:	Date Completed:
6.0	01/15/2022	GHS-535-DSC	01/2022

SECTION 1. IDENTIFICATION

Product Name: Dielectric Compound

Manufacturer or supplier's details

Company name of supplier: JIT Silicones Plus

Address: 5 Industrial Park Drive

Oakdale, PA 15071

Telephone: 855-548-7587

Emergency Telephone: 24 Hour Emergency Telephone:

CHEMTREC: (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use: Lubricant (not for medical purposes)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification: Not hazardous

GHS Labeling: Symbol: None

Signal Word: None

Hazard Statements: Not Hazardous

Precautionary Statements: Use personal protective equipment as required. Wear safety

glasses and gloves. Avoid contact with eyes.

Non-flammable or combustible, but may burn if involved in a

fire.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identity: Dimethyl phenylmethyl siloxane and silicones, 70-90%

Common Name: Methyl silicone CAS-No.: 63148-62-9

Impurities: No information provided by manufacturer

Chemical Identify: Silicon dioxide, amorphous 5-15%

Common Name: Amorphous fumed silica

CAS-No.: 112945-52-5

Impurities: Less than 1%, not classifiable

Chemical Identify: Dimethyl siloxane, hydroxy-terminated, 3-10%

Dielectric Compound

Version	on:	Revision Date:	MSDS Number:	Date Completed:
6.0		01/15/2022	GHS-535-DSC	01/2022

Common Name: Dimethyl silicone CAS-No.: 70131-67-8

Impurities: No information provided by manufacturer

SECTION 4. FIRST AID MEASURES

Eye Contact: Flush eyes with large amounts of water.

If signs/symptoms persist, get medical attention. Obtain

medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms

persist, get medical attention. No need for first aid is

anticipated.

Inhalation: If signs/symptoms develop, remove person to fresh air. If

signs/symptoms persist, get medical attention.

Ingestion: If swallowed, do not induce vomiting. If irritation or

discomfort occurs, obtain medical assistance.

SECTION 5. FIRE-FIGHTING MEASURES

Autoignition Temperature: >300°C Flash point: >300°C

Flammable Limits (LEL):

Flammable Limits (UEL):

Not determined

Not determined

Suitable Extinguishing Media: On large fires, use dry chemical, foam, or water spray. On

small fires use carbon dioxide, dry chemical, or water spray.

Water can be used to cool fire exposed containers.

Unsuitable Extinguishing Media: None.

Specific hazards in case of fire: Decomposes on heating and can release formaldehyde. Avoid

reaction with oxidizers.

Special protective equipment and

precautions for fire fighters:

No acute hazard. Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full

firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate

escape air supply. Use any self-contained breathing

apparatus with a full face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If

2

safe to do so, remove containers from path of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use appropriate personal protection. (See section 8.)

GHS-535-DSC

Dielectric Compound

Version:	Revision Date:	MSDS Number:	Date Completed:
6.0	01/15/2022	GHS-535-DSC	01/2022

Environmental precautions: For larger spills, cover drains and build dikes to prevent entry

> into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Methods for material for containment

and cleaning up:

Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin, inhalation of mist, or ingestion. See

> section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be

decontaminated.

Conditions for safe storage, including

any incompatibilities:

Store away from oxidizing materials. Store produce in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: Under most handling conditions, this product will not

generate mist or dust.

Engineering Controls: In most conditions, no special local ventilation is needed.

General ventilation recommended. If the product is heated

above 150°C or atomized, ventilation should be used.

Personal Protective Equipment (PPE):

Safety glasses recommended. Eyes:

Skin: Impermeable gloves should be worn. Product is compatible

with most elastomers.

Inhalation: No respiratory protection required under most conditions. If

concentrations exceed exposure limits, approved respiratory

equipment must be used.

Dielectric Compound

Version:	Revision Date:	MSDS Number:	Date Completed:
6.0	01/15/2022	GHS-535-DSC	01/2022

SECTION 9. CHEMICAL AND PHYSICAL PROPERTIES

Physical state: Solid. Liquid may separate from product.

Color: Off white, translucent

Odor: Mild

Odor Threshold:Not availablepH Value:Not applicableMelting Point:Decomposes

Freezing Point: Becomes very stiff with decreasing temperature around -75°C

Initial Boiling Point: >200°C

Flash point: >300°C COC (Base oil)

Evaporation rate:

Flammability (solid, gas):

Explosion limits:

Vapor pressure:

Vapor density:

Not available

Negligible at 20°C

Not available

Solubility: Insoluble in water at 20°C

Partition coefficient: Not available
Autoignition temperature: Not available

Decomposition temperature: Begins to decompose at 150°C.

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under ambient temperatures and pressures.

Possibility of hazardous reactions: May react with air under very high pressure. Otherwise will

not react or polymerize.

Conditions to avoid: No specific conditions to aboid have been identified.

Materials to avoid: Oxidizers

Hazardous decomposition products: Decomposes on heating and produces formaldehyde, silicone

dioxide, and incompletely burned carbon compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

(a) Acute toxicity: Methyl phenyl silicone LD50 (rat) >10,000 mg/kg (dimethyl silicone)

(b) Skin corrosion/irritation: Not irritating / not corrosive to the skin. LD50 (rabbit)>2,000 mg/kg (dimethyl silicone)

- (c) Serious eye damage/irritation: Possible irritant / not corrosive to the eyes.
- (d) Respiratory or skin sensitization: Not sensitizing to the skin.
- (e) Germ-cell mutagenicity. Not a germ cell mutagen.
- (f) Carcinogenicity. Not a carcinogen.
- **(g) Reproductive toxicity.** There are currently no reliable scientific data available indicating adverse effects on reproduction or fertility.
- (h) Aspiration hazard. Not applicable (not an aerosol/mist).

Dielectric Compound

Version:	Revision Date:	MSDS Number:	Date Completed:
6.0	01/15/2022	GHS-535-DSC	01/2022

SECTION 12. ECOLOGICAL INFORMATION

Toxicity: Invertebrates: Daphnia magna 48h-LC50>10,000mg/L

(dimethyl silicone)

Invertebrates: Daphnia magna 24h- LC50>10,000mg/L

(amorphous silica)

Fish: Brachydanio rerio 96h-LC50>10,000 mg/L (amorphous

silica)

Persistence and degradability: In soil, siloxanes are degraded.

Bioaccumulative potential: Not expected to bioaccumulate.

Mobility in soil: Siloxanes are removed from water by sedimentation or

binding to sewage sludge. Silica is not mobile.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods: Waste (substance and container material) shall be

recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste

management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized

landfill.

According to the European Waste

Catalogue:

Waste Codes are not product specific but application specific

Waste Codes should be assigned by the user based on the

application in which the product is used.

For USA Disposal: Waste must be disposed of in accordance with federal, state,

and local environmental control regulations.

SECTION 14. TRANSPORT INFORMATION

Class or Type: US DOT, IMO, ADR, RID, AND, IMDG, and IATA: Non-hazardous

SECTION 15. REGULATORY INFORMATION

Safety, health and environment regulations/legislation specific for the mixture:

5

Dielectric Compound

Version:	Revision Date:	MSDS Number:	Date Completed:
6.0	01/15/2022	GHS-535-DSC	01/2022

Other Information:

U.S. Regulatory Information

TSCA Inventory Status: All ingredients listed or exempt

TSCA 12 (b) Export Notification: Not listed

CERCLA Section 103 (40 CFR 302.4): N
SARA Section 302 (40 CFR 355.30): N
SARA Section 304 (40 CFR 355.40): N
SARA Section 313 (40 CFR 372.65): N
OSHA Process Safety (29 CFR 1910.119) N

SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21) -

Acute Hazard: N
Chronic Hazard: N
Fire Hazard: N
Reactivity Hazard: N
Sudden Release Hazard: N

State Regulations: Not on California Proposition 65 list. Does not contain any

contaminants or by-products known to the State of California

to cause cancer or reproductive toxicity.

Note – There are no known safety, health or environmental restrictions or prohibitions in any country where this product is

produced, imported or marketed.

Chemical Inventories:

DSL (Canada)

IECSC (Peoples Republic of China)

TSCA (United States of America)

All ingredients listed or exempt

All ingredients listed or exempt

All ingredients listed or exempt

SECTION 16. OTHER INFORMATION

NFPA Hazard Classification:

Health: 0
Flammability: 1
Reactivity: 0
Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification:

Health: 0
Flammability: 1
Reactivity: 0

Protection: B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

Dielectric Compound

Version:	Revision Date:	MSDS Number:	Date Completed:
6.0	01/15/2022	GHS-535-DSC	01/2022

These data are offered in good faith as typical values are not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.



HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

Sources of key data used to Compile the Material Safety Data Sheet: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Revision Date: 02/06/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8